

Teknisk informasjon RBKP-T

Modell Model	Artikkelnummer Item number	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBKP-T-1GN	07861010	44/64 kg	0,29 m ³
RBKP-T-1GN S	07861010	24/24 kg	0,29 m ³
RBKP-T-2GN	07862010	62 / 82 kg	0,42 m ³
RBKP-T-2GN S	07862010	42 / 62 kg	0,42 m ³
RBKP-T-3GN	07863010	84 / 104 kg	0,65 m ³
RBKP-T-3GN S	07863010	64 / 84 kg	0,65 m ³
RBKP-T-4GN	07864010	106 / 126 kg	0,85 m ³
RBKP-T-4GN S	07864010	86 / 106 kg	0,85 m ³
RBKP-T-5GN	07865010	128 / 148 kg	1,08 m ³
RBKP-T-5GN S	07865010	108 / 128 kg	1,08 m ³
RBKP-T-6GN	07866010	150 / 170 kg	1,38 m ³
RBKP-T-6GN S	07866010	130 / 150 kg	1,38 m ³

S= sentralkjøling / central cooling.

Modell Model	Mål Dimension	Strømart Kind of current
RBKP-T-1GN	460 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 140 W
RBKP-T-1GN S	460 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W
RBKP-T-2GN	785 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 140 W
RBKP-T-2GN S	785 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W
RBKP-T-3GN	1110 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 140 W
RBKP-T-3GN S	1110 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W
RBKP-T-4GN	1435 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 190 W
RBKP-T-4GN S	1435 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W
RBKP-T-5GN	1760 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 290 W
RBKP-T-5GN S	1760 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W
RBKP-T-6GN	2085 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 290 W
RBKP-T-6GN S	2085 x 650 x 870 mm (+30/-5 mm)	230 V - 1 – 50 HZ – 25 W

Modell Model	Kuldemedie Refrigerant	Kapillarrør Capillary tube	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBKP-T-1GN	R290 - 0,076 kg	Ø 0,8 – 1500 mm	
RBKP-T-1GN S			250 W /-10
RBKP-T-2GN	R290 - 0,076 kg	Ø 0,8 – 1500 mm	
RBKP-T-2GN S			250 W /-10
RBKP-T-3GN	R290 - 0,090 kg	Ø 1,0 – 3000 mm	
RBKP-T-3GN S			250 W /-10
RBKP-T-4GN	R290 - 0,100 kg	Ø 1,0 – 1800 mm	
RBKP-T-4GN S			350 W /-10
RBKP-T-5GN	R290 - 0,140 kg	Ø 0,8 – 2300 mm	
RBKP-T-5GN S			470 W /-10
RBKP-T-6GN	R290 - 0,140 kg	Ø 0,8 – 2000 mm	
RBKP-T-6GN S			470 W /-10

TD-500822 - Rev. 21. feb. 2025.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no